

2/6 POLAR COORDINATES (r - θ)

We now consider the third description of plane curvilinear motion, namely, polar coordinates where the particle is located by the radial distance r from a fixed point and by an angular measurement θ to the radial line. Polar coordinates are particularly useful when a motion is constrained through the control of a radial distance and an angular position or when an unconstrained motion is observed by measurements of a radial distance and an angular position.

Figure 2/13a shows the polar coordinates r and θ which locate a particle traveling on a curved path. An arbitrary fixed line, such as the x -axis, is used as a reference for the measurement of θ . Unit vectors \mathbf{e}_r and \mathbf{e}_θ are established in the positive r - and θ -directions, respectively. The position vector \mathbf{r} to the particle at A has a magnitude equal to the radial distance r and a direction specified by the unit vector \mathbf{e}_r . Thus, we express the location of the particle at A by the vector

$$\mathbf{r} = r\mathbf{e}_r$$

Time Derivatives of the Unit Vectors

To differentiate this relation with respect to time to obtain $\mathbf{v} = \dot{\mathbf{r}}$ and $\mathbf{a} = \dot{\mathbf{v}}$, we need expressions for the time derivatives of both unit vectors \mathbf{e}_r and \mathbf{e}_θ . We obtain $\dot{\mathbf{e}}_r$ and $\dot{\mathbf{e}}_\theta$ in exactly the same way we derived $\dot{\mathbf{e}}_t$ in the preceding article. During time dt the coordinate directions rotate through the angle $d\theta$, and the unit vectors also rotate through the same angle from \mathbf{e}_r and \mathbf{e}_θ to \mathbf{e}'_r and \mathbf{e}'_θ , as shown in Fig. 2/13b. We note that the vector change $d\mathbf{e}_r$ is in the plus θ -direction and that $d\mathbf{e}_\theta$ is in the minus r -direction. Because their magnitudes in the limit are equal to the unit vector as radius times the angle $d\theta$ in radians, we can write them as $d\mathbf{e}_r = \mathbf{e}_\theta d\theta$ and $d\mathbf{e}_\theta = -\mathbf{e}_r d\theta$. If we divide these equations by $d\theta$, we have

$$\frac{d\mathbf{e}_r}{d\theta} = \mathbf{e}_\theta \quad \text{and} \quad \frac{d\mathbf{e}_\theta}{d\theta} = -\mathbf{e}_r$$

If, on the other hand, we divide them by dt , we have $d\mathbf{e}_r/dt = (d\theta/dt)\mathbf{e}_\theta$ and $d\mathbf{e}_\theta/dt = -(d\theta/dt)\mathbf{e}_r$, or simply

$$\dot{\mathbf{e}}_r = \dot{\theta}\mathbf{e}_\theta \quad \text{and} \quad \dot{\mathbf{e}}_\theta = -\dot{\theta}\mathbf{e}_r \quad (2/12)$$


Velocity

We are now ready to differentiate $\mathbf{r} = r\mathbf{e}_r$ with respect to time. Using the rule for differentiating the product of a scalar and a vector gives


$$\mathbf{v} = \dot{\mathbf{r}} = \dot{r}\mathbf{e}_r + r\dot{\mathbf{e}}_r$$

With the substitution of $\dot{\mathbf{e}}_r$ from Eq. 2/12, the vector expression for the velocity becomes

$$\mathbf{v} = \dot{r}\mathbf{e}_r + r\dot{\theta}\mathbf{e}_\theta \quad (2/13)$$



(a)



(b)

Figure 2/13

where

$$\begin{aligned}v_r &= \dot{r} \\v_\theta &= r\dot{\theta} \\v &= \sqrt{v_r^2 + v_\theta^2}\end{aligned}$$

The r -component of \mathbf{v} is merely the rate at which the vector \mathbf{r} stretches. The θ -component of \mathbf{v} is due to the rotation of \mathbf{r} .

Acceleration

We now differentiate the expression for \mathbf{v} to obtain the acceleration $\mathbf{a} = \dot{\mathbf{v}}$. Note that the derivative of $r\dot{\theta}\mathbf{e}_\theta$ will produce three terms, since all three factors are variable. Thus,

$$\mathbf{a} = \dot{\mathbf{v}} = (\ddot{r}\mathbf{e}_r + \dot{r}\dot{\mathbf{e}}_r) + (\dot{r}\dot{\theta}\mathbf{e}_\theta + r\ddot{\theta}\mathbf{e}_\theta + r\dot{\theta}\dot{\mathbf{e}}_\theta)$$

Substitution of $\dot{\mathbf{e}}_r$ and $\dot{\mathbf{e}}_\theta$ from Eq. 2/12 and collecting terms give

$$\mathbf{a} = (\ddot{r} - r\dot{\theta}^2)\mathbf{e}_r + (r\ddot{\theta} + 2\dot{r}\dot{\theta})\mathbf{e}_\theta \quad (2/14)$$

where

$$\begin{aligned}a_r &= \ddot{r} - r\dot{\theta}^2 \\a_\theta &= r\ddot{\theta} + 2\dot{r}\dot{\theta} \\a &= \sqrt{a_r^2 + a_\theta^2}\end{aligned}$$

We can write the θ -component alternatively as

$$a_\theta = \frac{1}{r} \frac{d}{dt} (r^2 \dot{\theta})$$

which can be verified easily by carrying out the differentiation. This form for a_θ will be useful when we treat the angular momentum of particles in the next chapter.

Geometric Interpretation

The terms in Eq. 2/14 can be best understood when the geometry of the physical changes can be clearly seen. For this purpose, Fig. 2/14a is developed to show the velocity vectors and their r - and θ -components at position A and at position A' after an infinitesimal movement. Each of these components undergoes a change in magnitude and direction as shown in Fig. 2/14b. In this figure we see the following changes:

(a) Magnitude Change of \mathbf{v}_r . This change is simply the increase in length of v_r or $dv_r = d\dot{r}$, and the corresponding acceleration term is $d\dot{r}/dt = \ddot{r}$ in the positive r -direction.

(b) Direction Change of \mathbf{v}_r . The magnitude of this change is seen from the figure to be $v_r d\theta = \dot{r} d\theta$, and its contribution to the acceleration becomes $\dot{r} d\theta/dt = \dot{r}\dot{\theta}$ which is in the positive θ -direction.

(c) Magnitude Change of \mathbf{v}_θ . This term is the change in length of \mathbf{v}_θ or $d(r\dot{\theta})$, and its contribution to the acceleration is $d(r\dot{\theta})/dt = r\ddot{\theta} + \dot{r}\dot{\theta}$ and is in the positive θ -direction.




Figure 2/14

(d) Direction Change of \mathbf{v}_θ . The magnitude of this change is $v_\theta d\theta = r\dot{\theta} d\theta$, and the corresponding acceleration term is observed to be $r\dot{\theta}(d\theta/dt) = r\dot{\theta}^2$ in the negative r -direction.

Collecting terms gives $a_r = \ddot{r} - r\dot{\theta}^2$ and $a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$ as obtained previously. We see that the term \ddot{r} is the acceleration which the particle would have along the radius in the absence of a change in θ . The term $-r\dot{\theta}^2$ is the normal component of acceleration if r were constant, as in circular motion. The term $r\ddot{\theta}$ is the tangential acceleration which the particle would have if r were constant, but is only a part of the acceleration due to the change in magnitude of \mathbf{v}_θ when r is variable. Finally, the term $2\dot{r}\dot{\theta}$ is composed of two effects. The first effect comes from that portion of the change in magnitude $d(r\dot{\theta})$ of v_θ due to the change in r , and the second effect comes from the change in direction of \mathbf{v}_r . The term $2\dot{r}\dot{\theta}$ represents, therefore, a combination of changes and is not so easily perceived as are the other acceleration terms.

Note the difference between the vector change $d\mathbf{v}_r$ in \mathbf{v}_r and the change dv_r in the magnitude of v_r . Similarly, the vector change $d\mathbf{v}_\theta$ is not the same as the change dv_θ in the magnitude of v_θ . When we divide these changes by dt to obtain expressions for the derivatives, we see clearly that the magnitude of the derivative $|d\mathbf{v}_r/dt|$ and the derivative of the magnitude dv_r/dt are *not* the same. Note also that a_r is not \dot{v}_r and that a_θ is not \dot{v}_θ .

The total acceleration \mathbf{a} and its components are represented in Fig. 2/15. If \mathbf{a} has a component normal to the path, we know from our analysis of n - and t -components in Art. 2/5 that the sense of the n -component *must* be toward the center of curvature.




Figure 2/15

Circular Motion

For motion in a circular path with r constant, the components of Eqs. 2/13 and 2/14 become simply


$$\begin{aligned} v_r &= 0 & v_\theta &= r\dot{\theta} \\ a_r &= -r\dot{\theta}^2 & a_\theta &= r\ddot{\theta} \end{aligned}$$

This description is the same as that obtained with n - and t -components, where the θ - and t -directions coincide but the positive r -direction is in the negative n -direction. Thus, $a_r = -a_n$ for circular motion centered at the origin of the polar coordinates.

The expressions for a_r and a_θ in scalar form can also be obtained by direct differentiation of the coordinate relations $x = r \cos \theta$ and $y = r \sin \theta$ to obtain $a_x = \ddot{x}$ and $a_y = \ddot{y}$. Each of these rectangular components of acceleration can then be resolved into r - and θ -components which, when combined, will yield the expressions of Eq. 2/14.

Sample Problem 2/9

Rotation of the radially slotted arm is governed by $\theta = 0.2t + 0.02t^3$, where θ is in radians and t is in seconds. Simultaneously, the power screw in the arm engages the slider B and controls its distance from O according to $r = 0.2 + 0.04t^2$, where r is in meters and t is in seconds. Calculate the magnitudes of the velocity and acceleration of the slider for the instant when $t = 3$ s.



Solution. The coordinates and their time derivatives which appear in the expressions for velocity and acceleration in polar coordinates are obtained first and evaluated for $t = 3$ s.

$$\begin{aligned} r &= 0.2 + 0.04t^2 & r_3 &= 0.2 + 0.04(3^2) = 0.56 \text{ m} \\ \dot{r} &= 0.08t & \dot{r}_3 &= 0.08(3) = 0.24 \text{ m/s} \\ \ddot{r} &= 0.08 & \ddot{r}_3 &= 0.08 \text{ m/s}^2 \\ \theta &= 0.2t + 0.02t^3 & \theta_3 &= 0.2(3) + 0.02(3^3) = 1.14 \text{ rad} \\ & & & \text{or } \theta_3 = 1.14(180/\pi) = 65.3^\circ \\ \dot{\theta} &= 0.2 + 0.06t^2 & \dot{\theta}_3 &= 0.2 + 0.06(3^2) = 0.74 \text{ rad/s} \\ \ddot{\theta} &= 0.12t & \ddot{\theta}_3 &= 0.12(3) = 0.36 \text{ rad/s}^2 \end{aligned}$$

The velocity components are obtained from Eq. 2/13 and for $t = 3$ s are

$$\begin{aligned} [v_r = \dot{r}] & & v_r &= 0.24 \text{ m/s} \\ [v_\theta = r\dot{\theta}] & & v_\theta &= 0.56(0.74) = 0.414 \text{ m/s} \\ [v = \sqrt{v_r^2 + v_\theta^2}] & & v &= \sqrt{(0.24)^2 + (0.414)^2} = 0.479 \text{ m/s} \quad \text{Ans.} \end{aligned}$$

The velocity and its components are shown for the specified position of the arm.

The acceleration components are obtained from Eq. 2/14 and for $t = 3$ s are

$$\begin{aligned} [a_r = \ddot{r} - r\dot{\theta}^2] & & a_r &= 0.08 - 0.56(0.74)^2 = -0.227 \text{ m/s}^2 \\ [a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}] & & a_\theta &= 0.56(0.36) + 2(0.24)(0.74) = 0.557 \text{ m/s}^2 \\ [a = \sqrt{a_r^2 + a_\theta^2}] & & a &= \sqrt{(-0.227)^2 + (0.557)^2} = 0.601 \text{ m/s}^2 \quad \text{Ans.} \end{aligned}$$




The acceleration and its components are also shown for the 65.3° position of the arm.

Plotted in the final figure is the path of the slider B over the time interval $0 \leq t \leq 5$ s. This plot is generated by varying t in the given expressions for r and θ . Conversion from polar to rectangular coordinates is given by

$$x = r \cos \theta \quad y = r \sin \theta$$

Helpful Hint

- ① We see that this problem is an example of constrained motion where the center B of the slider is mechanically constrained by the rotation of the slotted arm and by engagement with the turning screw.



Sample Problem 2/10

A tracking radar lies in the vertical plane of the path of a rocket which is coasting in unpowered flight above the atmosphere. For the instant when $\theta = 30^\circ$, the tracking data give $r = 25(10^4)$ ft, $\dot{r} = 4000$ ft/sec, and $\dot{\theta} = 0.80$ deg/sec. The acceleration of the rocket is due only to gravitational attraction and for its particular altitude is 31.4 ft/sec² vertically down. For these conditions determine the velocity v of the rocket and the values of \ddot{r} and $\ddot{\theta}$.

Solution. The components of velocity from Eq. 2/13 are

$$[v_r = \dot{r}] \quad v_r = 4000 \text{ ft/sec}$$

$$\textcircled{1} [v_\theta = r\dot{\theta}] \quad v_\theta = 25(10^4)(0.80)\left(\frac{\pi}{180}\right) = 3490 \text{ ft/sec}$$

$$[v = \sqrt{v_r^2 + v_\theta^2}] \quad v = \sqrt{(4000)^2 + (3490)^2} = 5310 \text{ ft/sec}$$

Ans.

Since the total acceleration of the rocket is $g = 31.4$ ft/sec² down, we can easily find its r - and θ -components for the given position. As shown in the figure, they are

$$\textcircled{2} \quad a_r = -31.4 \cos 30^\circ = -27.2 \text{ ft/sec}^2$$

$$a_\theta = 31.4 \sin 30^\circ = 15.70 \text{ ft/sec}^2$$

We now equate these values to the polar-coordinate expressions for a_r and a_θ which contain the unknowns \ddot{r} and $\ddot{\theta}$. Thus, from Eq. 2/14

$$\textcircled{3} [a_r = \ddot{r} - r\dot{\theta}^2] \quad -27.2 = \ddot{r} - 25(10^4)\left(0.80 \frac{\pi}{180}\right)^2$$


$$\ddot{r} = 21.5 \text{ ft/sec}^2$$

Ans.

$$[a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}] \quad 15.70 = 25(10^4)\ddot{\theta} + 2(4000)\left(0.80 \frac{\pi}{180}\right)$$

$$\ddot{\theta} = -3.84(10^{-4}) \text{ rad/sec}^2$$

Ans.



Helpful Hints


- ① We observe that the angle θ in polar coordinates need not always be taken positive in a counterclockwise sense.
- ② Note that the r -component of acceleration is in the negative r -direction, so it carries a minus sign.
- ③ We must be careful to convert $\dot{\theta}$ from deg/sec to rad/sec.

$$r = 24 + l \Rightarrow \begin{aligned} \dot{r} &= \dot{l} \\ \ddot{r} &= \ddot{l} \end{aligned}$$

2/139 The boom OAB pivots about point O , while section AB simultaneously extends from within section OA . Determine the velocity and acceleration of the center B of the pulley for the following conditions: $\theta = 20^\circ$, $\dot{\theta} = 5 \text{ deg/sec}$, $\ddot{\theta} = 2 \text{ deg/sec}^2$, $l = 7 \text{ ft}$, $\dot{l} = 1.5 \text{ ft/sec}$, $\ddot{l} = -4 \text{ ft/sec}^2$. The quantities \dot{l} and \ddot{l} are the first and second time derivatives, respectively, of the length l of section AB .

Ans. $\mathbf{v} = 1.5\mathbf{e}_r + 2.71\mathbf{e}_\theta \text{ ft/sec}$

$\mathbf{a} = -4.24\mathbf{e}_r + 1.344\mathbf{e}_\theta \text{ ft/sec}^2$



$$\theta = 20^\circ$$

$$\dot{\theta} = 5 \text{ deg/sec}$$

$$\ddot{\theta} = 2 \text{ deg/sec}^2$$

$$r = 24 + 7 = 31 \text{ ft}$$

$$\dot{r} = \dot{l} = -4 \text{ ft/sec}$$

$$\ddot{r} = \ddot{l} = 1.5 \text{ ft/sec}^2$$

$$v_r = \dot{r} = 1.5 \text{ ft/sec}$$

$$v_\theta = r\dot{\theta} = 31 \times \frac{5\pi}{180} = 2.7 \text{ ft/sec}$$

$$v_r = \dot{r}$$

$$v_\theta = r\dot{\theta}$$

$$a_r = \ddot{r} - r\dot{\theta}^2$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$$

$$\dot{\theta} = 5 \frac{\text{deg}}{\text{sec}} = \frac{5\pi}{180} \frac{\text{rad}}{\text{sec}}$$

$$\ddot{\theta} = 2 \frac{\text{deg}}{\text{sec}^2} = \frac{2\pi}{180} \frac{\text{rad}}{\text{sec}^2}$$

$$\vec{v} = 1.5\mathbf{e}_r + 2.7\mathbf{e}_\theta \text{ ft/sec}$$


$$a_r = \ddot{r} - r\dot{\theta}^2 = -4 - 31 \times \left(\frac{5\pi}{180}\right)^2 = -4.236 \text{ ft/sec}^2$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta} = 31 \times \left(\frac{2\pi}{180}\right) + 2 \times 1.5 \times \left(\frac{5\pi}{180}\right) = 1.3439 \text{ ft/sec}^2$$

$$\vec{a} = -4.236\mathbf{e}_r + 1.344\mathbf{e}_\theta \text{ ft/sec}^2$$

2/147 The rocket is fired vertically and tracked by the radar station shown. When θ reaches 60° , other corresponding measurements give the values $r = 30,000$ ft, $\ddot{r} = 70$ ft/sec², and $\dot{\theta} = 0.02$ rad/sec. Calculate the magnitudes of the velocity and acceleration of the rocket at this position.

Ans. $v = 1200$ ft/sec, $a = 67.0$ ft/sec²



$$\sin 60 = \frac{v_\theta}{v}$$

$$v = \frac{v_\theta}{\sin 60}$$

$$a_r = \ddot{r} - r\dot{\theta}^2$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$$

$$a_r = 70 - 30,000 \times 0.02^2$$

$$\theta = 60^\circ$$

$$r = 30,000 \text{ ft}$$

$$\ddot{r} = 70 \text{ ft/sec}^2$$

$$\dot{\theta} = 0.02 \text{ rad/sec}$$

$$v, a = ?$$

$$v_\theta = r\dot{\theta}$$

$$= 30,000 \times 0.02 = 600 \text{ ft/sec}$$

$$v_r = \dot{r}$$

$$v_\theta = r\dot{\theta}$$

$$a_r = \ddot{r} - r\dot{\theta}^2$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$$

$$\tan 30 = \frac{v_\theta}{v_r}$$

$$v_r = \frac{v_\theta}{\tan 30} = \frac{600}{\tan 30}$$


$$\theta = 60^\circ$$

$$r = 30,000 \text{ ft}$$

$$\ddot{r} = 70 \text{ ft/sec}^2$$

$$\dot{\theta} = 0.02 \text{ rad/sec}$$

$$v, a = ?$$




$$a \cos 30 = a_r$$

$$a = \frac{a_r}{\cos 30}$$


2/151 Link AB rotates through a limited range of the angle β , and its end A causes the slotted link AC to rotate also. For the instant represented where $\beta = 60^\circ$ and $\dot{\beta} = 0.6 \text{ rad/s}$ constant, determine the corresponding values of \dot{r} , \ddot{r} , $\dot{\theta}$, and $\ddot{\theta}$. Make use of Eqs. 2/13 and 2/14.

Ans. $\dot{r} = 77.9 \text{ mm/s}$, $\ddot{r} = -13.5 \text{ mm/s}^2$
 $\dot{\theta} = -0.3 \text{ rad/s}$, $\ddot{\theta} = 0$



2/137 Motion of the sliding block P in the rotating radial slot is controlled by the power screw as shown. For the instant represented, $\dot{\theta} = 0.1 \text{ rad/s}$, $\ddot{\theta} = -0.4 \text{ rad/s}^2$, and $r = 300 \text{ mm}$. Also, the screw turns at a constant speed giving $\dot{r} = 40 \text{ mm/s}$. For this instant, determine the magnitudes of the velocity \mathbf{v} and acceleration \mathbf{a} of P . Sketch \mathbf{v} and \mathbf{a} if $\theta = 120^\circ$.

Ans. $v = 50 \text{ mm/s}$, $a = 5 \text{ mm/s}^2$



$$\begin{aligned} v_r &= \dot{r} \\ v_\theta &= r\dot{\theta} \\ a_r &= \ddot{r} - r\dot{\theta}^2 \end{aligned}$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta}$$

$$\dot{\theta} = 0.1 \text{ rad/sec}$$

$$\ddot{\theta} = -0.4 \text{ rad/sec}^2$$

$$r = 300 \text{ mm}$$

$$\dot{r} = 40 \text{ mm/sec}$$

$$\theta = 120^\circ$$

$$v_r = 40 \text{ mm/sec} = 0.04 \text{ m/sec}$$

$$v_\theta = r\dot{\theta} = 0.3 \times 0.1 \text{ rad/sec} = 0.03 \text{ m/sec}$$

$$v = \sqrt{v_r^2 + v_\theta^2} = \sqrt{0.04^2 + 0.03^2} = 0.05 \text{ m/sec}$$

$$v = 50 \text{ mm/sec}$$

$$a_r = \ddot{r} - r\dot{\theta}^2 = 0 - 0.3 \times 0.1^2 = -0.003 \text{ m/sec}^2$$

$$a_\theta = r\ddot{\theta} + 2\dot{r}\dot{\theta} = 0.3 \times (-0.4) + 2 \times 0.04 \times 0.1 = 0.128 \text{ m/sec}^2$$

$$a = \sqrt{(-0.003)^2 + (0.128)^2} =$$