

2/3 PLANE CURVILINEAR MOTION

We now treat the motion of a particle along a curved path which lies in a single plane. This motion is a special case of the more general three-dimensional motion introduced in Art. 2/1 and illustrated in Fig. 2/1. If we let the plane of motion be the x - y plane, for instance, then the coordinates z and ϕ of Fig. 2/1 are both zero, and R becomes the same as r . As mentioned previously, the vast majority of the motions of points or particles encountered in engineering practice can be represented as plane motion.

Before pursuing the description of plane curvilinear motion in any specific set of coordinates, we will first use vector analysis to describe the motion, since the results will be independent of any particular coordinate system. What follows in this article constitutes one of the most basic concepts in dynamics, namely, the *time derivative of a vector*. Much analysis in dynamics utilizes the time rates of change of vector quantities. You are therefore well advised to master this topic at the outset because you will have frequent occasion to use it.

Consider now the continuous motion of a particle along a plane curve as represented in Fig. 2/5. At time t the particle is at position A , which is located by the *position vector* \mathbf{r} measured from some convenient fixed origin O . If both the magnitude and direction of \mathbf{r} are known at time t , then the position of the particle is completely specified. At time $t + \Delta t$, the particle is at A' , located by the position vector $\mathbf{r} + \Delta\mathbf{r}$. We note, of course, that this combination is vector addition and not scalar addition. The *displacement* of the particle during time Δt is the vector $\Delta\mathbf{r}$ which represents the vector change of position and is clearly independent of the choice of origin. If an origin were chosen at some different location, the position vector \mathbf{r} would be changed, but $\Delta\mathbf{r}$ would be unchanged. The *distance* actually traveled by the particle as it moves along the path from A to A' is the scalar length Δs measured along the path. Thus, we distinguish between the vector displacement $\Delta\mathbf{r}$ and the scalar distance Δs .

Velocity

The *average velocity* of the particle between A and A' is defined as $\mathbf{v}_{av} = \Delta\mathbf{r}/\Delta t$, which is a vector whose direction is that of $\Delta\mathbf{r}$ and whose magnitude is the magnitude of $\Delta\mathbf{r}$ divided by Δt . The average speed of




Figure 2/5

the particle between A and A' is the scalar quotient $\Delta s/\Delta t$. Clearly, the magnitude of the average velocity and the speed approach one another as the interval Δt decreases and A and A' become closer together.

The *instantaneous velocity* \mathbf{v} of the particle is defined as the limiting value of the average velocity as the time interval approaches zero. Thus,

$$\mathbf{v} = \lim_{\Delta t \rightarrow 0} \frac{\Delta \mathbf{r}}{\Delta t}$$

We observe that the direction of $\Delta \mathbf{r}$ approaches that of the tangent to the path as Δt approaches zero and, thus, the velocity \mathbf{v} is always a vector tangent to the path.

We now extend the basic definition of the derivative of a scalar quantity to include a vector quantity and write

$$\mathbf{v} = \frac{d\mathbf{r}}{dt} = \dot{\mathbf{r}} \quad (2/4)$$

The derivative of a vector is itself a vector having both a magnitude and a direction. The magnitude of \mathbf{v} is called the *speed* and is the scalar

$$v = |\mathbf{v}| = \frac{ds}{dt} = \dot{s}$$

At this point we make a careful distinction between the *magnitude of the derivative* and the *derivative of the magnitude*. The magnitude of the derivative can be written in any one of the several ways $|d\mathbf{r}/dt| = |\dot{\mathbf{r}}| = \dot{s} = |\mathbf{v}| = v$ and represents the magnitude of the velocity, or the speed, of the particle. On the other hand, the derivative of the magnitude is written $d|\mathbf{r}|/dt = dr/dt = \dot{r}$, and represents the rate at which the length of the position vector \mathbf{r} is changing. Thus, these two derivatives have two entirely different meanings, and we must be extremely careful to distinguish between them in our thinking and in our notation. For this and other reasons, you are urged to adopt a consistent notation for handwritten work for all vector quantities to distinguish them from scalar quantities. For simplicity the underline \underline{v} is recommended. Other handwritten symbols such as \vec{v} , \mathcal{V} , and \hat{v} are sometimes used.

With the concept of velocity as a vector established, we return to Fig. 2/5 and denote the velocity of the particle at A by the tangent vector \mathbf{v} and the velocity at A' by the tangent \mathbf{v}' . Clearly, there is a vector change in the velocity during the time Δt . The velocity \mathbf{v} at A plus (vectorially) the change $\Delta \mathbf{v}$ must equal the velocity at A' , so we can write $\mathbf{v}' - \mathbf{v} = \Delta \mathbf{v}$. Inspection of the vector diagram shows that $\Delta \mathbf{v}$ depends both on the change in magnitude (length) of \mathbf{v} and on the change in direction of \mathbf{v} . These two changes are fundamental characteristics of the derivative of a vector.

Acceleration

The *average acceleration* of the particle between A and A' is defined as $\Delta \mathbf{v}/\Delta t$, which is a vector whose direction is that of $\Delta \mathbf{v}$. The magnitude of this average acceleration is the magnitude of $\Delta \mathbf{v}$ divided by Δt .

The *instantaneous acceleration* \mathbf{a} of the particle is defined as the limiting value of the average acceleration as the time interval approaches zero. Thus,

$$\mathbf{a} = \lim_{\Delta t \rightarrow 0} \frac{\Delta \mathbf{v}}{\Delta t}$$

By definition of the derivative, then, we write

$$\mathbf{a} = \frac{d\mathbf{v}}{dt} = \dot{\mathbf{v}} \quad (2/5)$$

As the interval Δt becomes smaller and approaches zero, the direction of the change $\Delta \mathbf{v}$ approaches that of the differential change $d\mathbf{v}$ and, thus, of \mathbf{a} . The acceleration \mathbf{a} , then, includes the effects of both the change in magnitude of \mathbf{v} and the change of direction of \mathbf{v} . It is apparent, in general, that the direction of the acceleration of a particle in curvilinear motion is neither tangent to the path nor normal to the path. We do observe, however, that the acceleration component which is normal to the path points toward the center of curvature of the path.

Visualization of Motion

A further approach to the visualization of acceleration is shown in Fig. 2/6, where the position vectors to three arbitrary positions on the path of the particle are shown for illustrative purpose. There is a velocity vector tangent to the path corresponding to each position vector, and the relation is $\mathbf{v} = \dot{\mathbf{r}}$. If these velocity vectors are now plotted from some arbitrary point C , a curve, called the *hodograph*, is formed. The derivatives of these velocity vectors will be the acceleration vectors $\mathbf{a} = \dot{\mathbf{v}}$ which are tangent to the hodograph. We see that the acceleration has the same relation to the velocity as the velocity has to the position vector.

The geometric portrayal of the derivatives of the position vector \mathbf{r} and velocity vector \mathbf{v} in Fig. 2/5 can be used to describe the derivative of any vector quantity with respect to t or with respect to any other scalar variable. Now that we have used the definitions of velocity and acceleration to introduce the concept of the derivative of a vector, it is important to establish the rules for differentiating vector quantities. These rules




Figure 2/6

are the same as for the differentiation of scalar quantities, except for the case of the cross product where the order of the terms must be preserved. These rules are covered in Art. C/7 of Appendix C and should be reviewed at this point.

Three different coordinate systems are commonly used for describing the vector relationships for curvilinear motion of a particle in a plane: rectangular coordinates, normal and tangential coordinates, and polar coordinates. An important lesson to be learned from the study of these coordinate systems is the proper choice of a reference system for a given problem. This choice is usually revealed by the manner in which the motion is generated or by the form in which the data are specified. Each of the three coordinate systems will now be developed and illustrated.

2/4 RECTANGULAR COORDINATES (x-y)

This system of coordinates is particularly useful for describing motions where the x- and y-components of acceleration are independently generated or determined. The resulting curvilinear motion is then obtained by a vector combination of the x- and y-components of the position vector, the velocity, and the acceleration.

Vector Representation

The particle path of Fig. 2/5 is shown again in Fig. 2/7 along with x- and y-axes. The position vector **r**, the velocity **v**, and the acceleration **a** of the particle as developed in Art. 2/3 are represented in Fig. 2/7 together with their x- and y-components. With the aid of the unit vectors **i** and **j**, we can write the vectors **r**, **v**, and **a** in terms of their x- and y-components. Thus,

$$\begin{aligned} \mathbf{r} &= x\mathbf{i} + y\mathbf{j} \\ \mathbf{v} &= \dot{\mathbf{r}} = \dot{x}\mathbf{i} + \dot{y}\mathbf{j} \\ \mathbf{a} &= \dot{\mathbf{v}} = \ddot{\mathbf{r}} = \ddot{x}\mathbf{i} + \ddot{y}\mathbf{j} \end{aligned}$$

(2/6)

As we differentiate with respect to time, we observe that the time derivatives of the unit vectors are zero because their magnitudes and directions remain constant. The scalar values of the components of **v** and **a** are merely $v_x = \dot{x}$, $v_y = \dot{y}$ and $a_x = \dot{v}_x = \ddot{x}$, $a_y = \dot{v}_y = \ddot{y}$. (As drawn in Fig. 2/7, a_x is in the negative x-direction, so that \ddot{x} would be a negative number.)

As observed previously, the direction of the velocity is always tangent to the path, and from the figure it is clear that

$$\begin{aligned} v^2 &= v_x^2 + v_y^2 & v &= \sqrt{v_x^2 + v_y^2} & \tan \theta &= \frac{v_y}{v_x} \\ a^2 &= a_x^2 + a_y^2 & a &= \sqrt{a_x^2 + a_y^2} \end{aligned}$$

If the angle θ is measured counterclockwise from the x-axis to **v** for the configuration of axes shown, then we can also observe that $dy/dx = \tan \theta = v_y/v_x$.




Figure 2/7

If the coordinates x and y are known independently as functions of time, $x = f_1(t)$ and $y = f_2(t)$, then for any value of the time we can combine them to obtain \mathbf{r} . Similarly, we combine their first derivatives \dot{x} and \dot{y} to obtain \mathbf{v} and their second derivatives \ddot{x} and \ddot{y} to obtain \mathbf{a} . On the other hand, if the acceleration components a_x and a_y are given as functions of the time, we can integrate each one separately with respect to time, once to obtain v_x and v_y and again to obtain $x = f_1(t)$ and $y = f_2(t)$. Elimination of the time t between these last two parametric equations gives the equation of the curved path $y = f(x)$.

From the foregoing discussion we can see that the rectangular-coordinate representation of curvilinear motion is merely the superposition of the components of two simultaneous rectilinear motions in the x - and y -directions. Therefore, everything covered in Art. 2/2 on rectilinear motion can be applied separately to the x -motion and to the y -motion.

Projectile Motion

An important application of two-dimensional kinematic theory is the problem of projectile motion. For a first treatment of the subject, we neglect aerodynamic drag and the curvature and rotation of the earth, and we assume that the altitude change is small enough so that the acceleration due to gravity can be considered constant. With these assumptions, rectangular coordinates are useful for the trajectory analysis.

For the axes shown in Fig. 2/8, the acceleration components are

$$a_x = 0 \quad a_y = -g$$

Integration of these accelerations follows the results obtained previously in Art. 2/2a for constant acceleration and yields

$$\begin{aligned} v_x &= (v_x)_0 & v_y &= (v_y)_0 - gt \\ x &= x_0 + (v_x)_0 t & y &= y_0 + (v_y)_0 t - \frac{1}{2}gt^2 \\ v_y^2 &= (v_y)_0^2 - 2g(y - y_0) \end{aligned}$$

In all these expressions, the subscript zero denotes initial conditions, frequently taken as those at launch where, for the case illustrated,





Figure 2/8

$x_0 = y_0 = 0$. Note that the quantity g is taken to be positive throughout this text.




We can see that the x - and y -motions are independent for the simple projectile conditions under consideration. Elimination of the time t between the x - and y -displacement equations shows the path to be parabolic (see Sample Problem 2/6). If we were to introduce a drag force which depends on the speed squared (for example), then the x - and y -motions would be coupled (interdependent), and the trajectory would be nonparabolic.

When the projectile motion involves large velocities and high altitudes, to obtain accurate results we must account for the shape of the projectile, the variation of g with altitude, the variation of the air density with altitude, and the rotation of the earth. These factors introduce considerable complexity into the motion equations, and numerical integration of the acceleration equations is usually necessary.



This stroboscopic photograph of a bouncing ping-pong ball suggests not only the parabolic nature of the path, but also the fact that the speed is lower near the apex.

$$\begin{aligned} x &= v_0 \cos \theta t \rightarrow t = \frac{x}{v_0 \cos \theta} \\ y &= -\frac{1}{2} g t^2 + v_0 \sin \theta t \rightarrow y = -\frac{1}{2} g \left(\frac{x^2}{v_0^2 \cos^2 \theta} \right) + v_0 \sin \theta \left(\frac{x}{v_0 \cos \theta} \right) \\ y &= \frac{-g}{2 v_0^2 \cos^2 \theta} x^2 + \tan \theta x \end{aligned}$$



$$\begin{cases} v_x = v_0 \cos \theta \\ v_y = -gt + v_0 \sin \theta \end{cases} \xrightarrow{\text{Eq. 1}} v_y = 0 \rightarrow t = \frac{v_0 \sin \theta}{g}$$

$$R = v_0 \cos \theta \times \frac{2v_0 \sin \theta}{g}$$

$$R = \frac{2v_0^2 \sin \theta \cos \theta}{g} = \frac{v_0^2 \sin 2\theta}{g}$$

Sample Problem 2/5

The curvilinear motion of a particle is defined by $v_x = 50 - 16t$ and $y = 100 - 4t^2$, where v_x is in meters per second, y is in meters, and t is in seconds. It is also known that $x = 0$ when $t = 0$. Plot the path of the particle and determine its velocity and acceleration when the position $y = 0$ is reached.

Solution. The x -coordinate is obtained by integrating the expression for v_x , and the x -component of the acceleration is obtained by differentiating v_x . Thus,

$$\left[\int dx = \int v_x dt \right] \quad \int_0^x dx = \int_0^t (50 - 16t) dt \quad x = 50t - 8t^2 \text{ m}$$

$$[a_x = \dot{v}_x] \quad a_x = \frac{d}{dt}(50 - 16t) \quad a_x = -16 \text{ m/s}^2$$

The y -components of velocity and acceleration are

$$[v_y = \dot{y}] \quad v_y = \frac{d}{dt}(100 - 4t^2) \quad v_y = -8t \text{ m/s}$$

$$[a_y = \dot{v}_y] \quad a_y = \frac{d}{dt}(-8t) \quad a_y = -8 \text{ m/s}^2$$

We now calculate corresponding values of x and y for various values of t and plot x against y to obtain the path as shown.

When $y = 0$, $0 = 100 - 4t^2$, so $t = 5$ s. For this value of the time, we have

$$v_x = 50 - 16(5) = -30 \text{ m/s}$$

$$v_y = -8(5) = -40 \text{ m/s}$$

$$v = \sqrt{(-30)^2 + (-40)^2} = 50 \text{ m/s}$$

$$a = \sqrt{(-16)^2 + (-8)^2} = 17.89 \text{ m/s}^2$$



The velocity and acceleration components and their resultants are shown on the separate diagrams for point A, where $y = 0$. Thus, for this condition we may write

$$\mathbf{v} = -30\mathbf{i} - 40\mathbf{j} \text{ m/s}$$

Ans.

$$\mathbf{a} = -16\mathbf{i} - 8\mathbf{j} \text{ m/s}^2$$

Ans.



Helpful Hint

We observe that the velocity vector lies along the tangent to the path as it should, but that the acceleration vector is not tangent to the path. Note especially that the acceleration vector has a component that points toward the inside of the curved path. We concluded from our diagram in Fig. 2/5 that it is impossible for the acceleration to have a component that points toward the outside of the curve.

Sample Problem 2/6

A rocket has expended all its fuel when it reaches position A, where it has a velocity of u at an angle θ with respect to the horizontal. It then begins unpowered flight and attains a maximum added height h at position B after traveling a horizontal distance s from A. Determine the expressions for h and s , the time t of flight from A to B, and the equation of the path. For the interval concerned, assume a flat earth with a constant gravitational acceleration g and neglect any atmospheric resistance.

Solution. Since all motion components are directly expressible in terms of horizontal and vertical coordinates, a rectangular set of axes x - y will be employed. With the neglect of atmospheric resistance, $a_x = 0$ and $a_y = -g$, and the resulting motion is a direct superposition of two rectilinear motions with constant acceleration. Thus,

$$[dx = v_x dt] \quad x = \int_0^t u \cos \theta dt \quad x = ut \cos \theta$$

$$[dv_y = a_y dt] \quad \int_{u \sin \theta}^{v_y} dv_y = \int_0^t (-g) dt \quad v_y = u \sin \theta - gt$$

$$[dy = v_y dt] \quad y = \int_0^t (u \sin \theta - gt) dt \quad y = ut \sin \theta - \frac{1}{2}gt^2$$

Position B is reached when $v_y = 0$, which occurs for $0 = u \sin \theta - gt$ or

$$t = (u \sin \theta)/g \quad \text{Ans.}$$

Substitution of this value for the time into the expression for y gives the maximum added altitude

$$h = u \left(\frac{u \sin \theta}{g} \right) \sin \theta - \frac{1}{2}g \left(\frac{u \sin \theta}{g} \right)^2 \quad h = \frac{u^2 \sin^2 \theta}{2g} \quad \text{Ans.}$$


The horizontal distance is seen to be

$$s = u \left(\frac{u \sin \theta}{g} \right) \cos \theta \quad s = \frac{u^2 \sin 2\theta}{2g} \quad \text{Ans.}$$

which is clearly a maximum when $\theta = 45^\circ$. The equation of the path is obtained by eliminating t from the expressions for x and y , which gives

$$y = x \tan \theta - \frac{gx^2}{2u^2} \sec^2 \theta \quad \text{Ans.}$$

③ This equation describes a vertical parabola as indicated in the figure.



Helpful Hints


① Note that this problem is simply the description of projectile motion neglecting atmospheric resistance.

$$\begin{cases} x = u \cos \theta t \\ y = -\frac{1}{2}gt^2 + u \sin \theta t \end{cases} \rightarrow \begin{cases} v_x = u \cos \theta \\ v_y = -gt + u \sin \theta \end{cases}$$

② We see that the total range and time of flight for a projectile fired above a horizontal plane would be twice the respective values of s and t given here.

③ If atmospheric resistance were to be accounted for, the dependency of the acceleration components on the velocity would have to be established before an integration of the equations could be carried out. This becomes a much more difficult problem.

2/72 With what minimum horizontal velocity u can a boy throw a rock at A and have it just clear the obstruction at B?



$$B \begin{vmatrix} 40 \\ -10 \end{vmatrix}$$


$$y = \frac{-g}{2u^2} x^2$$

$$-10 = \frac{-9,81}{2u^2} \times 40^2$$

$$\rightarrow u = \sqrt{\quad}$$

2/79 A projectile is launched from point A with the initial conditions shown in the figure. Determine the slant distance s which locates the point B of impact. Calculate the time of flight t .

Ans. $s = 1057 \text{ m}$, $t = 19.50 \text{ s}$



$$B \begin{cases} 800 + S \cos 20 \\ -S \sin 20 \end{cases}$$

$$y = \frac{-g}{2v_0^2 \cos^2 \theta} x^2 + \tan \theta x$$

$$-S \sin 20 = \frac{-9.81}{2 \times 120^2 \times \cos^2 40} (800 + S \cos 20)^2 + \tan 40 \times (800 + S \cos 20)$$

$$S = \checkmark$$



$$\checkmark$$

$$y = -\frac{1}{2} g t^2 + v_0 \sin \theta t \rightarrow -S \sin 20 = -\frac{1}{2} \times 9.81 \times t^2 + 120 \times \sin 40 \times t$$


$$\rightarrow t = \checkmark$$

2/85 A projectile is launched with an initial speed of 200 m/s at an angle of 60° with respect to the horizontal. Compute the range R as measured up the incline.

Ans. $R = 2970$ m



$$\begin{cases} x = -\frac{1}{2} g \sin^2 20^\circ t^2 + v_0 \cos 40^\circ t \\ y = -\frac{1}{2} g \cos^2 20^\circ t^2 + v_0 \sin 40^\circ t \end{cases}$$



$$R = \sqrt{x_1^2 + y_1^2}$$

$$y = \frac{-g}{2v_0^2 \cos^2 \theta} x^2 + \tan \theta x$$

$$y = \tan \alpha x$$


$$\tan \alpha x = \frac{-g}{2v_0^2 \cos^2 \theta} x^2 + \tan \theta x$$

$$\rightarrow x = \sqrt{\quad}$$

$$y_1 = \sqrt{\quad}$$

2/87 The muzzle velocity of a long-range rifle at A is $u = 400$ m/s. Determine the two angles of elevation θ which will permit the projectile to hit the mountain target B.

Ans. $\theta_1 = 26.1^\circ$, $\theta_2 = 80.6^\circ$



$$y = \frac{-g}{2u^2 \cos^2 \theta} x^2 + \tan \theta x$$

$$\begin{array}{l} 5000 \\ 1500 \end{array}$$

$$1500 = \frac{-9.81}{2 \times 400^2 \times \cos^2 \theta} \times 5000^2 + \tan \theta \times 5000$$

$$\frac{1}{\cos^2 \theta} = 1 + \tan^2 \theta$$

